



AIR CONDITIONING



REFRIGERATION



HEATING



maxi orange

CONDENSATE REMOVAL PUMP



Need more performance? Designed for larger units, the Maxi Orange pump gives you the extra power when you need it.



35L/h max. flow



15m max. rec. head (flow rate 10L/h)



35dB(A)

KEY FEATURES





- High power motor
- Superior performance
- Submersible secondary reservoir included

SUITABILITY

- Up to 46kW / 157,000Btu/h
- High wall split systems; Ducted units; Floor standing & Chassis units
- ✓ **Perfect for...** Large commercial units



0.45 kg†



MAXI ORANGE SPECIFICATIONS

Max. flow	35L/h @ 0 head
Max. rec. head	15m
Max. suction lift	2m
Sound level@1m	35dB(A)
Power supply	230 VAC, 0.11A, 16W, 50/60Hz
Rated Class	Non continuous II appliance <input type="checkbox"/>
Max. unit output	46kW / 157,000Btu/h
Max. water temp	40°C / 104°F
Discharge tube	6mm ID
IP Protection	IP21
Safety switch	3.0A Normally closed
Thermal protection	✓
Fully potted	✓
Self priming	✓

MAXI ORANGE OPTIONS

Maxi Orange (Europe)	FP2210
† Pump only	

SUGGESTED XTRA ACCESSORIES

Description	Part No.
1 Amp Fuse	FP2620
Tube To Soil Stack Adaptor	FP2038
Vinyl Tube Braided 1/4" (6mm)	AX5100
Inline Filter 16mm	FP2640
4.3m mini/maxi orange extension kit	FP2940

IN THE BOX

- Maxi Orange pump
- 1.5m Plug & play power cable
- Reservoir
- Reservoir lid with 1.5m sensor cable
- Submersible reservoir
- Anti siphon device
- Float & filter
- 1.5m Suction tube 6mm ID
- 220mm Orange inlet hose 14mm ID
- 150mm Vinyl breather tube 6mm ID
- Drain connector kit
- Fixing kit
- Install manual

- Download manual at aspenspumps.com
- View install video at aspenspumps.com

For more installation accessories take a look at our Aspen Xtra range

Information correct at time of going to press.

