

SPIN TOOLS



HEAT BY FRICTION



AVOID CRACKS AND LEAKS



10X FASTER



FITS ANY DRILL



410A COMPATIBLE



HVAC READY

Spin
TOOLS

These flaring and swaging tools are designed for most tubing diameters, and they allow you to connect tubes without the need for extra fittings (swage), and preserves the copper malleability (flare) thus preventing cracks and leaks.



| Part code | Description |
|------------------------------|------------------------------|
| FLARING TOOL SETS | |
| F4000 | 1/4, 3/8, 1/2, 5/8 |
| F5000 | 1/4, 3/8, 1/2, 5/8, 3/4 |
| F6000 | 1/4, 3/8, 1/2, 5/8, 3/4, 7/8 |
| SWAGING TOOL SETS | |
| S4000 | 1/4, 3/8, 1/2, 5/8 |
| S5000 | 1/4, 3/8, 1/2, 5/8, 3/4 |
| S6000 | 1/4, 3/8, 1/2, 5/8, 3/4, 7/8 |
| P3000 | PLUMBING 1/2, 3/4, 1" |
| FLARING HEADS, INCHES | |
| F1014 | 1/4" |
| F1516 | 5/16" |
| F1038 | 3/8" |
| F1012 | 1/2" |
| F1058 | 5/8" |
| F1034 | 3/4" |
| F1078 | 7/8" |

| Part code | Description |
|------------------------------|------------------------------|
| SWAGING HEADS, INCHES | |
| S1014 | 1/4" |
| S1516 | 5/16" |
| S1038 | 3/8" |
| S1012 | 1/2" |
| S1058 | 5/8" |
| S1034 | 3/4" |
| S1078 | 7/8" |
| S6000 | 1/4, 3/8, 1/2, 5/8, 3/4, 7/8 |
| P3000 | PLUMBING 1/2, 3/4, 1" |
| FLARING TOOL SETS | |
| F4000 | 1/4, 3/8, 1/2, 5/8 |
| F5000 | 1/4, 3/8, 1/2, 5/8, 3/4 |
| F6000 | 1/4, 3/8, 1/2, 5/8, 3/4, 7/8 |
| SWAGING TOOL SETS | |
| S4000 | 1/4, 3/8, 1/2, 5/8 |
| S5000 | 1/4, 3/8, 1/2, 5/8, 3/4 |
| S6000 | 1/4, 3/8, 1/2, 5/8, 3/4, 7/8 |

| Part code | Description |
|------------------------------|-------------|
| FLARING HEADS, INCHES | |
| F1014 | 1/4" |
| F1516 | 5/16" |
| F1038 | 3/8" |
| F1012 | 1/2" |
| F1058 | 5/8" |
| F1034 | 3/4" |
| F1078 | 7/8" |
| SWAGING HEADS, INCHES | |
| S1014 | 1/4" |
| S1516 | 5/16" |
| S1038 | 3/8" |
| S1012 | 1/2" |
| S1058 | 5/8" |
| S1034 | 3/4" |
| S1078 | 7/8" |

| Part code | Description |
|-------------|---|
| SPIN-CASE-S | Soft Deluxe Case - swaging |
| SPIN-CASE-F | Soft Deluxe Case - flaring |
| SPIN-X6000 | Swaging / flaring tool set - 1/4", 3/8" & 1/2" in soft case |