




BULLDOG A2L DV

Spark Proof Dual Voltage Vacuum Pump

- Spark Proof design:
- Integrated On/Off switch.
- 5 m hard wired cable to suit 115 V* or 230 V.
- Dual voltage – switch easily to 115 V* or 230 V.
- Two stage oil sealed vacuum pump.
- Isolation solenoid valve.
- Dual oil mist filters to prevent oil mist



Dual oil mist filters to prevent oil mist

Isolation solenoid valve

Two stage oil sealed vacuum pump



JAVAC MEASURED PERFORMANCE	
Model: BULLDOG	VBD1622 (UK, JAV-1075 (EU))
Free Air Displacement	156 l/m, 5.5 CFM
Ultimate Vacuum	15 Microns
Power Supply (AC)	240V 50/60
Motor	2880 RPM
Stages	2
Oil Capacity	450 ml

Use only JAVAC genuine oil HVU11 HVU16
DO NOT overfill - oil must be visible in sight glass.
Change oil regularly to ensure best performance.
www.javac.co.uk



Spark proof!
Integrated spark proof power switch, lead and circuit breaker

Part No.	VBD1622
Suitability	All standard and A2L applications

SPECIFICATION

Stage	Double
Ultimate vacuum	15 microns
Free air displacement	156 l/m (5.5 CFM)
Power supply	115V* or 230 V
Motor size	2880 rpm
Power cord	Glanded
Oil capacity	450 ml
Intake fittings	1/4", 5/16", 3/8" SAE
Weight	12.5 kg
Dimensions	338 x 212 x 238 mm



*115V cable sold separately.