



## VAMP-F

Condensate Pump

NEW PRODUCT



# Condensate Pump with minimal space requirement

**Quick and easy to install, highly versatile, exceptionally quiet, and the smallest of its kind on the market – this is the new condensate pump from the VAMP series.**

It combines innovative technology with practical benefits. Proven and interference-resistant optical sensor technology is paired with the reliable and silent operation of a diaphragm pump. In the development process, we focused on using as few components as possible to make installation and handling easy and fast for the user.

The VAMP-F features an integrated reservoir and an optical level sensor, making it the smallest model on the market.

**Minimal space requirement:** Standing at just 26 mm tall, it fits in even the tightest spaces

**Quiet operation:** Thanks to advanced diaphragm pump technology and effective vibration dampening, the pump operates at less than 20 dB(A)

**Easy and quick installation:** The posable hose serves as a reservoir replacement (with filter and adapter) for direct connection to the condensate tray

**Versatile applications:** Suitable for wall-mounted units, ceiling units, and floor units

**Pump Capacity:** Handles up to 22 liters per hour

**Discharge height:** Capable of up to 15 meters

**Integrated switching power supply:** Operates universally with input voltages ranging from 100-240 VAC

**Optical level sensing technology:** Reliable operation ensured by proven optical sensor

**Manufactured in Switzerland**



## Specification

Property	Value
Maximum flow rate	22 l/h (6 GPH)
Maximum discharge height	15 m (49 ft)
Maximum horizontal run	75 m at 0 m head and 0 m suction (246 ft at 0 ft head and 0 ft suction)
Pump type	Diaphragm pump
Electrical ratings	100-240 VAC, 50/60 Hz, 6 W, Protection Class II
Alarm relay rating	Normally-closed, failsafe 250 VAC, 5 A or 30 VDC, 5 A
Ingress protection	Fully potted IP67 / cable connector IP44
Operating temperature	3 °C – 40 °C (37 °F – 104 °F)
Water temperature	3 °C – 40 °C (37 °F – 104 °F)
Storage temperature	-20 °C – 70 °C (-4 °F – 158 °F)
Noise level	< 20 dB(A)
Compliance	CE

### Spare parts and accessories:

<b>POSABLE-HOSE/4</b> (with filter)	4689088
<b>KIT-4087</b> (Star tube & Anti-Siphon)	3004087
<b>STAR-TUBE-600</b> (15 m / 50 ft)	3004186
<b>PVC-TUBE</b> (¾" / 6 mm, 30 m / 98 ft)	4679160
<b>INLINE-FILTER</b>	4678597
<b>CP-INSTALLATION-CABLE</b>	4689089
<b>HSG-4065/4</b> (Anti-Siphon)	3004065

## Pictures

